



SPM-D11 Series

Load Share Synchronizer

APPLICATIONS

The SPM-D11 is a microprocessor-based synchronizer designed for use on one or three-phase AC generators equipped with Woodward or other compatible speed controls and automatic voltage regulators. The SPM-D11 synchronizer provides automatic frequency, phase and voltage matching using either analog- or discrete output bias signals.

It combines synchronizing for one circuit breaker, load and power factor control or isochronous load sharing and generator protection.

DESCRIPTION

Synchronizing

- Phase match or slip frequency synchronization with voltage matching
- Two-phase sensing of generator and bus
- Selectable operating modes like SPM-A (Run, Check, Permissive, and OFF)
- Synchro-check possible
- Synchronization time monitoring
- Load/var sharing

Mains parallel operation

- Real power control
- True RMS power calculation
- Generator real power setpoint by parameter (2 values) or via 0/4 to 20 mA
- Soft unloading
- Power factor control
- Power factor setpoint by parameter
- Power limit value with relay output

Isolated operation

- Frequency control
- Voltage control

Dead bus operation

- Closing of breaker on demand

FURTHER SPM-D SYNCHRONIZERS

- The SPM-D10 Series provides two-phase generator and bus measurement refer to product specifications 37297 for more information
- The SPM-D10/YB Series provides three-phase generator and bus measurement refer to product specifications 37298 for more information
- The SPM-D21 Series provides synchronizing for two circuit breakers and load control refer to product specifications 37293 for more information

DESCRIPTION

Protection

ANSI

- Single-phase CT sensing for generator
- Two-phase sensing of generator voltage
- Generator over-/undervoltage (59/27)
- Generator over-/underfrequency (81O/U)
- Generator reverse/reduced power (32R/F)
- Generator overload (32)

Control outputs

Standard

- Discrete raise/lower for speed/load
- Discrete raise/lower for voltage/power factor

LSXR Package

- Analog bias outputs for voltage and speed freely configurable for all levels (+/-1 V, +/-3 V, 0 to 5 V, 0.5 to 4.5 V, +/-10 V +/-5 V, 0 to 20 mA, +/-20 mA, and much more configurable)
- Speed bias output configurable as 500 Hz PWM output and adjustable voltage level
- Two raise/lower outputs configurable for either speed or voltage

Operating Features

- Two-line Liquid Crystal display for operation and alarm indication
- Synchroscope
- Indication of control activity and breaker state
- Multi-level password protection for parameters
- Configuration directly or via PC
- English or German language adjustable


- Load/var sharing
- Generator protection
- Synchronization for one circuit breaker
- Frequency, phase, and voltage matching
- Selectable types of control output
- Digital display of generator and bus values
- Real power control
- Power factor control
- PC and front panel configurable
- Microprocessor technology for flexible and reliable operation
- CE marked
- UL/cUL listed

1. *Journal of the American Medical Association*, 2000; 283: 2689-2693.


Relay outputs	isolated
Contact material	AgCdO
Load (GP).....	2.00 Aac@250 Vac
	2.00 Adc@24 Vdc / 0.36 Adc@125 Vdc / 0.18 Adc@250 Vdc
Pilot duty (PD)	
	1.00 Adc@24 Vdc / 0.22 Adc@125 Vdc / 0.10 Adc@250 Vdc
Housing.....	Type APRANORM DIN 43 700
Dimensions	144×72×122 mm
Front cutout	138[+1.0]×67[+0.7] mm
Connection	screw/plug terminals depending on connector 1.5 mm² or 2.5 mm²
Front.....	insulating surface
Protection system.....	with correct installation
	Front..... IP42
	(sealed IP54; gasket kit = P/N 8923-1037)
	Back..... IP21
Weight.....	depending on version, approx. 800 g
CE approval	tested according to applicable EN guidelines
Listings	UL/cUL listed (voltages up to 300 Vac)



APPLICATION DIAGRAM



APPLICATION EXAMPLES



International
Woodward
PO Box 1519
Fort Collins CO, USA
80522-1519
1000 East Drake Road
Fort Collins CO 80525
Ph: +1 (970) 482-5811
Fax: +1 (970) 498-3058

Europe
Woodward Governor Company
Leonhard-Reglerbau GmbH
Handwerkstrasse 29
70565 Stuttgart, Germany
Ph: +49 (0) 711 789 54-0
Fax: +49 (0) 711 789 54-100

Distributors & Service
Woodward has an international network of distributors and service facilities. For your nearest representative, call the Fort Collins plant or see the Worldwide Directory on our website.

Corporate Headquarters
Rockford IL, USA
Ph: +1 (815) 877-7441

www.woodward.com/power

For more information contact:

Subject to technical modifications.

This document is distributed for informational purposes only. It is not to be construed as creating or becoming part of any Woodward Governor Company contractual or warranty obligation unless expressly stated in a written sales contract.

We appreciate your comments about the content of our publications. Please send comments including the document number below to stgt-doc@woodward.com

© Woodward Governor Company

All Rights Reserved

37292C - 06/3/S

FEATURES OVERVIEW

SPM-D Series Synchronizer	SPM-D11/LSR 12/24 Vdc	SPM-D11/LSXR 12/24 Vdc	SPM-D11/LSR 24 Vdc	SPM-D11/LSXR 24 Vdc
Measuring/Display				
Generator voltage, 2phase	✓	✓	✓	✓
Generator current, 1phase	✓	✓	✓	✓
Busbar voltage, 2phase	✓	✓	✓	✓
Control				
Breaker	1	1	1	1
Synchronization, 2phase	✓	✓	✓	✓
Isolated operation	✓	✓	✓	✓
Mains parallel operation #1	✓	✓	✓	✓
SPM-A synchronization modes	✓	✓	✓	✓
Dead bus operation	✓	✓	✓	✓
Protection				
Generator: over-/undervoltage (59/27)	✓	✓	✓	✓
Generator: over-/underfrequency (81O/U)	✓	✓	✓	✓
Generator: overload (32)	✓	✓	✓	✓
Generator: reverse power (32R)	✓	✓	✓	✓
Generator: reduced power (32F)	✓	✓	✓	✓
Controller				
Discrete raise/lower: speed & load	✓	✓#2	✓	✓#2
Discrete raise/lower: voltage & power factor	✓	✓#2	✓	✓#2
Analog output: speed & load		✓		✓
Analog output: voltage & power factor		✓		✓
PMW output: speed & load		✓		✓
Active power setpoint: 0/4 to 20 mA	✓	✓	✓	✓
Load/var sharing	✓	✓	✓	✓
I/O's				
Alarm relays	3	3	3	3
Signalling relays	3	3	3	3
Listings/Approvals				
CE marked	✓	✓	✓	✓
UL/cUL listed	✓	✓	✓	✓
Accessories				
Configuration via PC #3	✓	✓	✓	✓
Manuals (for other languages please refer to the Woodward homepage)				
English	37259	37259	37259	37259
German	GR37259	GR37259	GR37259	GR37259
Voltage ratings				
Power supply	12/24 Vdc	12/24 Vdc	24 Vdc	24 Vdc
Discrete inputs	12/24 Vdc	12/24 Vdc	18 to 250 Vac/dc	18 to 250 Vac/dc
Part numbers P/N				
Measuring inputs 100 Vac, ..1 A			8440-1708	
Measuring inputs 100 Vac, ..5 A	8440-1703	8440-1706		8440-1713
Measuring inputs 400 Vac, ..1 A #4				
Measuring inputs 400 Vac, ..5 A #4	8440-1686	8440-1666		8440-1715

#1 Additional mains decoupling relay like MFR11 required

#2 configurable to either speed/load or voltage/power factor

#3 Cable incl. software necessary (DPC)

#4 All units with 400V measuring inputs can also be used for 100V system voltage